

**LANDI**

# C20 Pro C20 Pro SE

Android Desktop POS  
Terminal



**Future-ready SoftPOS power in an  
all-in-one performance hub.**

[www.landiglobal.com](http://www.landiglobal.com)

- Enhance user perception with interactive design.
- Tackle peak hours with seamless and speedy printing.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.
- Maximize counter flexibility with detachable CFD customer display.



## SPECIFICATIONS

<b>Processor</b>	Qualcomm Octa-core, up to 2.4GHz	<b>Size</b>	360mm x 235mm x 360mm (Terminal only)
<b>OS</b>	Android 13 GMS	<b>Connectivity</b>	Wi-Fi: IEEE802.11 a/b/g/n/ac 2.4GHz and 5GHz ETH: 1000M Bluetooth 5.0, support BLE Optional, 4G fallback 3G and GPRS (Only for C20 Pro 4G)
<b>Memory</b>	Internal: 4GB RAM+64GB FLASH 8GB RAM+128GB FLASH (Optional) External: Micro SD Card (Up to 2TB)	<b>Positioning</b> (Only For C20 Pro 4G)	Optional, GPS, GLONASS, BEIDOU
<b>Main display</b>	15.6", 1920x1080, FHD capacitive multi-touch	<b>Audio</b>	Speaker: 5W, 100dB@1m, Dual Speaker Headset: 3.5mm audio jack MIC: Dual Microphone
<b>Customer display</b>	Optional 1: None Optional 2: Standard CFD attached (10.1", 1280x800 px) Optional 3: Premium CFD attached/unattached (10.1" 1280x800 px, touch, QR camera, NFC) Optional 4: 15.6", 1920x1080, attached, capacitive multi-touch, NFC, no camera	<b>Camera</b> (Optional)	Optional 1 : NONE Optional 2 : 0.3M pixels, QR code scan (Only supported on the 10.1" Premium CFD)
<b>Ports</b>	1*USB Type-C 4*USB Type-A 2.0 + 1*USB Type-A 3.0 1*Micro USB (15.6" CFD: 2*Micro USB, Expansion Slot) 1*RJ22 Serial port 1*RJ45 Ethernet port 1*RJ11 Cash drawer port 1*3.5mm Audio jack 1*Micro SD slot 1*Power port	<b>NFC</b>	Android NFC, EMV Contactless L1 V3.1 compliant, Supports ISO / IEC 14443 Type A / B (Only supported on the 10.1" Premium CFD)
<b>Buttons</b>	1 Power key with indicator light (Red&blue) 2 Volume keys	<b>SAM/SIM slots</b> (Only For C20 Pro 4G)	1 SIM (Optional)
		<b>PSU</b>	19~20V/3.25A
		<b>Environment</b>	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +60°C Operating humidity: 10% to 90% non-condensing
		<b>Certification</b>	CE/CB/FCC/IC/RoHS/WEEE
		<b>Printer</b> (Only For C20 Pro)	80mm Thermal Printer, Diameter: 80mm Print speed: 200mm/s, Auto Cutter

