## LANDI



LANDI Empowering Connections Creating a Digital Future

## Unleash your terminal's potential with unshakeable support

The C20 SE is a perfect combination of stability, lightweight construction, durability, and aesthetics, desianed to deliver a seamless customer experience right at the point of interaction.

0

www.landiglobal.com

- The durable aluminum alloy design with a triangular base offers stability and balance
- Engage consumers with a large multimedia touchscreen and user-friendly interface
- Intuitive cable management for a clean and professional look



## **SPECIFICATIONS**

| Processor           | Quad-core, 2.0GHz  | Weight                   | Single-display : Net weight 3.9 kg, Gross weight 5.7 kg<br>Dual-display: Net weight 4.5 kg, Gross weight 6.4 kg                        |
|---------------------|--|--------------------------|--|
| OS                  | Android 13   |                          |  |
| Memory              | Internal:<br>4GB RAM+32GB FLASH<br>External:<br>Micro SD Card (Up to 2TB)  | Audio                    | Speaker:5W,100dB@1m, Dual Speaker<br>MIC: Dual Microphone<br>Headset: 3.5mm audio jack   |
|                     |  | Connectivity             | Wi-Fi: IEEE802.11 a/b/g/n/ac/ax 2.4G and 5G<br>ETH:1000M<br>Bluetooth 5.0, support BLE   |
| Main<br>Display     | 15.6",1920x1080,FHD<br>capacitive multi-touch  | <b>NFC</b><br>(Optional) | Android NFC<br>SO/IEC14443、1S015693 compliant<br>supportType A/B, Mifare, Felica<br>(Only supported on the 10.1'Premium CFD)           |
| Customer<br>Display | Optional 1:None<br>Optional 2: 10.1" Standard CFD<br>(1280x800 display only)<br>Optional 3:10.1"Premium CFD<br>(1280x800,Touch panel, QR Camera, NFC)  |                          |  |
|                     |  | Camera                   | Optional 1: NONE<br>Optional 2: 0.3M pixels, QR code scan<br>(Only supported on the 10.1'Premium CFD)                                  |
| Ports               | 1 USB Typec-C debug port,<br>1 Power port, 4*USB Type-A 2.0,<br>1 USB Type-A 3.0, 1*RJ22 Serial Port<br>1 Micro SD slot, 1*RJ45 Ethernet port<br>1 RJ11 Cash drawer port<br>1 3.5mm Audio jack |                          |  |
|                     |  | Power Supply             | 19V/3.42A  |
|                     |  | Environment              | Operating temperature :<br>0°C to +40°C<br>Storage temperature :<br>-20°C to +70°C<br>Operating humidity:<br>10% to 90% non-condensing |
| Buttons             | 1 Power key with indicator light<br>2 Volume keys  |                          |  |
| Size                | 400mm (L) x 284mm (W) x 402mm (H)<br>15.75" x 11.18" x 15.83"  | Certification            | CE/CB/FCC/IC/WEEE/RoHS   |

## LVNDI



LANDI reserves the right to modify or update any information provided herein without prior notice, including the design, construction, materials, processing, or specifications of any products. Additionally, LANDI may discontinue or restrict the production or distribution of any products.