

LANDI

C20 Pro C20 Pro SE

Android Desktop POS
Terminal



**Future-ready SoftPOS power in an
all-in-one performance hub.**

- Enhance user perception with interactive design.
- Tackle peak hours with seamless and speedy printing.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.



| SPECIFICATIONS

Processor	Qualcomm Octa-core, up to 2.4GHz	Size	360mm x 235mm x 360mm (Terminal only)
OS	Android 13 GMS	Connectivity	Wi-Fi: IEEE802.11 a/b/g/n/ac 2.4GHz and 5GHz ETH: 1000M Bluetooth 5.0, support BLE Optional, 4G fallback 3G and GPRS (Only for C20 Pro 4G)
Memory	Internal: 4GB RAM+64GB FLASH 8GB RAM+128GB FLASH (Optional) External: Micro SD Card (Up to 2TB)	Positioning (Only For C20 Pro 4G)	Optional, GPS, GLONASS, BEIDOU
Main display	15.6", 1920x1080, FHD capacitive multi-touch	Audio	Speaker: 5W, 100dB@1m, Dual Speaker Headset: 3.5mm audio jack MIC: Dual Microphone
Customer display	Optional 1: None Optional 2: 10.1" Standard CFD (1280x800 display only) Optional 3: 10.1" Premium CFD (1280x800, Touch panel, QR Camera, NFC)	Camera (Optional)	Optional 1 : NONE Optional 2 : 0.3M pixels, QR code scan (Only supported on the 10.1" Premium CFD)
Printer (Only For C20 Pro)	80mm Thermal Printer, Diameter: 80mm Print speed: 200mm/s, Auto Cutter	NFC	Android NFC, EMV Contactless L1 V3.1 compliant, Supports ISO / IEC 14443 Type A / B (Only supported on the 10.1" Premium CFD)
Ports	1*USB Type-C 4*USB Type-A 2.0 + 1*USB Type-A 3.0 1*Micro USB (15.6" CFD: 2*Micro USB, Expansion Slot) 1*RJ22 Serial port 1*RJ45 Ethernet port 1*RJ11 Cash drawer port 1*3.5mm Audio jack 1*Micro SD slot 1*Power port	SAM/SIM slots (Only For C20 Pro 4G)	1 SIM (Optional)
Buttons	1 Power key with indicator light (Red&blue) 2 Volume keys	PSU	19~20V/3.25A
		Environment	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +60°C Operating humidity: 10% to 90% non-condensing
		Certification	CE/CB/FCC/IC/RoHS/WEEE

