LANDI

C20 Pro

Android Desktop POS Terminal

Future-ready SoftPOS power in an all-in-one performance hub.

www.landiglobal.com

- Enhance user perception with interactive design.
- Tackle peak hours with seamless and speedy printing.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.
- Maximize counter flexibility with detachable CFD customer display.

SPECIFICATIONS

Processor	64-bit octa-core ARM Cortex
Operating System	Android 13 (GMS)
Memory	Internal: 4GB RAM + 64GB FLASH 8GB RAM + 128GB FLASH (Optional) Expansion: MicroSD card, up to 2TB
Main Display	15.6", 1920 × 1080, capacitive multi-touch 178° viewing angle
Customer-Facing Display	Option 1: None Option 2: 10.1" premium CFD (1280 × 800, touch panel, camera, NFC) Option 3: 15.6" premium CFD (1920 × 1080, touch panel, micro USB HOST, NFC)
Buttons	1*Power button with indicator light 2*Volume button 1*Function button
Camera	Front camera: 0.3MP, QR code scan (Optional) **Only supported on the 10.1" premium CFD*
Printer	Thermal printer Paper Width: 80 mm Roll Diameter: 80 mm Print Speed: 250 mm/s max Auto cutter
Audio	5W, 100dB@1m, Dual speakers 1*Headset via 3.5mm audio jack (CTIA&OTMP) 2*Microphone
Connectivity	WAN: 4G/3G/2G fallback (Optional) Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz LAN: 1000 Mbps Bluetooth: Bluetooth 5.0, supports BLE
Positioning (Optional)	AGPS, GPS, GLONASS, BeiDou, Galileo (Optional)

Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
NFC (Optional)	Android NFC, ISO/IEC 14443, ISO15693 compliant, Supports Type A/B Mifare, FeliCa (Optional) **Only supported on the 10.1"/15.6" premium CFD*
SIM/SAM Slots (Optional)	1*SIM
Power	100V-240V AC, 50-60Hz input; 19V DC, 3.42A output
Dimensions (L × W × H)	361.5 × 234 × 364 mm (Single display version) (Terminal only)
Weight	4.4kg (Single display version) (Terminal only) 5kg (Dual display version) (Terminal only)
Operating Temp.	0°C to +40°C (32°F to 104°F)
Storage Temp.	-20°C to +60°C (-4°F to 140°F)
Operating Humidity	5% to 95% (Non-condensing)
Certifications & Compliance	PCI:PCI MPoC Regulatory:CE, CB, FCC, IC, RoHS, WEEE, UN 38.3, DGM, GMS, ANATEL, PTCRB, NOM, CRT, BSMI, NCC
Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer

Rev. 2026.09.30

LANDI

This document is not binding and the specifications above can be modified without prior consent.