

LANDi

C20 Pro SE

Android Desktop POS
Terminal



**Future-ready SoftPOS power in an
all-in-one performance hub.**

www.landiglobal.com

- Enhance user perception with interactive design.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.
- Maximize counter flexibility with detachable CFD customer display.



SPECIFICATIONS

Processor	64-bit octa-core ARM Cortex (4x 2.4GHz A73 + 4x 1.9GHz A53)	NFC (Optional)	Android NFC, ISO/IEC 14443, ISO15693 compliant, Supports Type A/B Mifare, FeliCa <i>*Only supported on the 10.1"/15.6" premium CFD</i>
Operating System	Android 13 (GMS)	Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
Memory	Internal: 4GB RAM + 64GB FLASH 8GB RAM + 128GB FLASH (Optional) Expansion: MicroSD card, up to 2TB		
Main Display	15.6", 1920 × 1080, capacitive multi-touch		
Customer-Facing Display	Option 1: None Option 2: 10.1" premium CFD (1280 × 800, touch panel, camera, NFC) Option 3: 15.6" premium CFD (1920 × 1080, touch panel, micro USB HOST, NFC)		
Buttons	1*Power button with indicator light 2*Volume button 1*Function button	Dimensions (L × W × H)	361.5 × 234 × 364 mm (Single display version)
Camera	Front: 0.3MP, QR code scan (Optional) <i>*Only supported on the 10.1" premium CFD</i>	Weight	3.9kg (Single display version)
Audio	2*Speaker, 2*Microphone, Headset via 3.5mm audio jack	Operating Temp.	0°C to +40°C
Connectivity	Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz LAN: 1000 Mbps Bluetooth: Bluetooth 5.0, supports BLE	Storage Temp.	-20°C to +60°C
Power	100V-240V AC, 50-60Hz input; 19V DC, 3.42A output	Operating Humidity	10% to 90% (Non-condensing)
Certifications & Compliance	CE, CB, FCC, IC, RoHS, WEEE	Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer

Rev. 2026.06.30



This document is not binding and the specifications above can be modified without prior consent.

