

LANDI

C20 SE

ECR Terminal



Unleash your terminal's potential with unshakeable support

The C20 SE is a perfect combination of stability, lightweight construction, durability, and aesthetics, designed to deliver a seamless customer experience right at the point of interaction.

www.landiglobal.com

- The durable aluminum alloy design with a triangular base offers stability and balance
- Engage consumers with a large multimedia touchscreen and user-friendly interface
- Intuitive cable management for a clean and professional look



SPECIFICATIONS

Processor	Quad-core, 2.0GHz	Weight	Single-display : Net weight 3.9 kg, Gross weight 5.7 kg Dual-display: Net weight 4.5 kg, Gross weight 6.4 kg
OS	Android 13	Audio	Speaker:5W,100dB@1m, Dual Speaker MIC: Dual Microphone Headset: 3.5mm audio jack
Memory	Internal: 4GB RAM+32GB FLASH External: Micro SD Card (Up to 2TB)	Connectivity	Wi-Fi: IEEE802.11 a/b/g/n/ac/ax 2.4G and 5G ETH:1000M Bluetooth 5.0, support BLE
Main Display	15.6",1920x1080,FHD capacitive multi-touch	NFC (Optional)	Android NFC SO/IEC14443、1S015693 compliant supportType A/B, Mifare, Felica (Only supported on the 10.1'Premium CFD)
Customer Display	Optional 1:None Optional 2: 10.1" Standard CFD (1280x800 display only) Optional 3:10.1"Premium CFD (1280x800,Touch panel, QR Camera, NFC)	Camera	Optional 1: NONE Optional 2: 0.3M pixels, QR code scan (Only supported on the 10.1'Premium CFD)
Ports	1 USB Type-C debug port, 1 Power port, 4*USB Type-A 2.0, 1 USB Type-A 3.0, 1*RJ22 Serial Port 1 Micro SD slot, 1*RJ45 Ethernet port 1 RJ11 Cash drawer port 1 3.5mm Audio jack	Power Supply	19V/3.42A
Buttons	1 Power key with indicator light 2 Volume keys	Environment	Operating temperature : 0℃ to +40℃ Storage temperature : -20℃ to +60℃ Operating humidity: 10% to 90% non-condensing
Size	400mm (L) x 284mm (W) x 402mm (H) 15.75" x 11.18" x 15.83"	Certification	CE/CB/FCC/IC/WEEE/RoHS



This document is not binding and the specifications above can be modified without prior consent.

