

LANDI

Cx20 Cx20 SE

Windows Desktop POS Terminal



Feature-rich Windows platform for advanced efficiency.

The Cx20 Series features a hexa-core processor with performance of up to **4.4GHz** along with 8GB RAM and 256GB storage, making it perfectly compatible with **Windows 11 IoT**.

- **Expansive Touch Display:** 15.6" FHD IPS touch screen for vivid, responsive interaction.
- **Efficient Printing Solution** (Only on Cx20): Integrated 80mm thermal printer with auto-cutter for quick transaction records.
- **High-Speed Connectivity:** Dual-band Wi-Fi and 1000M Ethernet for seamless communication.



| SPECIFICATIONS

Processor	Hexa-core Intel i3, up to 4.4GHz	Camera	Front camera: 2MP, QR code scan (Optional) <i>*Only supported on the 10.1" premium CFD</i>
Operating System	Windows 11 IoT LTSC	Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
Memory	Internal: 8GB RAM + 256GB FLASH 8GB RAM + 512GB FLASH (Optional) 16GB RAM + 256GB FLASH (Optional) 16GB RAM + 512GB FLASH (Optional) <i>*Available SSD capacity may differ from labeled capacity due to system calculations and backup reserves. Actual space is shown in system display.</i>	Power	Cx20:100V-240V AC, 50-60Hz input; 19-20V DC, 4.74A output Cx20 SE:100V-240V AC, 50-60Hz input; 19V DC, 3.42A output
Main Display	15.6", 1920 × 1080, capacitive multi-touch 178° viewing angle	Dimensions (L × W × H)	361.5 × 234 × 364 mm (Single display version) (Terminal only)
Customer-Facing Display	Option 1: None Option 2: 10.1" standard CFD (1280 × 800) Option 3: 10.1" premium CFD (1280 × 800, touch panel, camera) Option 4: 15.6" standard CFD (1920 × 1080, micro USB HOST) Option 5: 15.6" premium CFD (1920 × 1080, touch panel, micro USB HOST)	Weight	Cx20:4.4kg (Single display version) (Terminal only) Cx20 SE:3.9kg (Single display version) (Terminal only)
Buttons	1*Power button with indicator light	Operating Temp.	0°C to +40°C (32°F to 104°F)
Connectivity	Wi-Fi: IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6E, 2.4Ghz/5Ghz/6Ghz, 2x2 MIMO LAN: 1000 Mbps Bluetooth: Bluetooth 5.3, supports BLE	Storage Temp.	-20°C to +60°C (-4°F to 140°F)
Audio	5W, 100dB@1m, Dual speakers, 2*Microphone 1*Headset via 3.5mm audio jack (CTIA&OTMP)	Operating Humidity	5% to 95% (Non-condensing)
Printer (Only on Cx20)	Thermal printer Paper Width: 80 mm Roll Diameter: 80 mm Print Speed: 250 mm/s max Auto cutter	Certifications & Compliance	CE, CB, FCC, IC, RoHS, WEEE, UN 38.3, DGM, ANATEL
		Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer

