LANDI

Cx20
Cx20 SE

Windows Desktop POS Terminal

Feature-rich Windows platform for advanced efficiency.

The Cx20 Series features a hexa-core processor with performance of up to **4.4GHz** along with 8GB RAM and 256GB storage, making it perfectly compatible with **Windows 11 IoT.**

www.landiglobal.com

- **Expansive Touch Display:** 15.6" FHD IPS touch screen for vivid, responsive interaction.
- **Efficient Printing Solution** (Only on Cx20)**:** Integrated 80mm thermal printer with auto-cutter for quick transaction records.
- **High-Speed Connectivity:** Dual-band Wi-Fi and 1000M Ethernet for seamless communication.

SPECIFICATIONS

Processor	Hexa-core Intel i3, up to 4.4GHz
Operating System	Windows 11 IoT LTSC
Memory	Internal: 8GB RAM + 256GB FLASH 8GB RAM + 512GB FLASH (Optional) 16GB RAM + 256GB FLASH (Optional) 16GB RAM + 512GB FLASH (Optional) **Available SSD capacity may differ from labeled capacity due to system calculations and backup reserves. Actual space is shown in system display.*
Main Display	15.6", 1920 × 1080, capacitive multi-touch
Customer-Facing Display	Option 1: None Option 2: 10.1" standard CFD (1280 × 800, 350 nits) Option 3: 10.1" premium CFD (1280 × 800, 350 nits, touch panel, camera) Option 4: 15.6" standard CFD (1920 × 1080, 300 nits, micro USB HOST) Option 5: 15.6" premium CFD (1920 × 1080, 300 nits, touch panel, micro USB HOST)
Buttons	1*Power button with indicator light
Connectivity	Wi-Fi: IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6E, 2.4Ghz/5Ghz/6Ghz, 2x2 MIMO LAN: 1000 Mbps Bluetooth: Bluetooth 5.3, supports BLE
Audio	5W, 100dB@1m, Dual speakers, 2*Microphone 1*Headset via 3.5mm audio jack (CTIA&OTMP)
Printer (Only on Cx20)	Thermal printer Paper Width: 80 mm Roll Diameter: 80 mm Print Speed: 250 mm/s max Auto cutter

Camera	Front camera: 2MP, QR code scan (Optional) **Only supported on the 10.1" premium CFD*
Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
Power	Cx20:100V-240V AC, 50-60Hz input; 19-20V DC, 4.74A output Cx20 SE:100V-240V AC, 50-60Hz input; 19V DC, 3.42A output
Dimensions (L × W × H)	361.5 × 234 × 364 mm (Single display version) (Terminal only)
Weight	Cx20:4.4kg (Single display version) (Terminal only) Cx20 SE:3.9kg (Single display version) (Terminal only)
Operating Temp.	0°C to +40°C
Storage Temp.	-20°C to +60°C
Operating Humidity	10% to 90% (Non-condensing)
Certifications & Compliance	CE, CB, FCC, IC, RoHS, WEEE, UN 38.3, DGM, ANATEL
Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer

Rev. 2026.08.31

LAVDI

This document is not binding and the specifications above can be modified without prior consent.