

LANDI

Cx20

Cx30

Windows Desktop POS Terminal



Feature-rich Windows platform for advanced efficiency.

The Cx20 & Cx30 deliver powerful, future-ready performance for Windows environments. Featuring a hexa-core processor on the Cx20 and a deca-core processor on the Cx30-both clocked up to 4.4 GHz-along with up to 16 GB RAM and 512 GB storage, the series is fully optimized for Windows 11 IoT.

www.landiglobal.com

- **Expansive Touch Display:** 15.6" FHD IPS touch screen for vivid, responsive interaction.
- **Efficient Printing Solution:** Integrated 80mm thermal printer with auto-cutter for quick transaction records.
- **High-Speed Connectivity:** Dual-band Wi-Fi and 1000M Ethernet for seamless communication.



SPECIFICATIONS

Processor	Cx20: Hexa-core Intel i3, up to 4.4GHz Cx30: Deca-core Intel i5, up to 4.4GHz	Audio	2*Speaker , 2*Microphone Headset via 3.5mm audio jack
Operating System	Windows 11 IoT LTSC	Camera	Front: 2MP, QR code scan (Optional) <i>*Only supported on the 10.1" premium CFD</i>
Memory	Internal: 8GB RAM + 256GB FLASH 8GB RAM + 512GB FLASH (Optional) 16GB RAM + 256GB FLASH (Optional) 16GB RAM + 512GB FLASH (Optional) <i>*Available SSD capacity may differ from labeled capacity due to system calculations and backup reserves. Actual space is shown in system display.</i>	Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
Main Display	15.6", 1920 × 1080, capacitive multi-touch	Power	100V-240V AC, 50-60Hz input; 19-20V DC, 4.74A output
Customer-Facing Display	Option 1: None Option 2: 10.1" standard CFD (1280 × 800) Option 3: 10.1" premium CFD (1280 × 800, touch panel, camera) Option 4: 15.6" standard CFD (1920 × 1080, micro USB HOST) Option 5: 15.6" premium CFD (1920 × 1080, touch panel, micro USB HOST)	Dimensions (L × W × H)	361.5 × 234 × 364 mm (Single display version)
Buttons	1*Power button with indicator light	Weight	4.4kg (Single display version)
Printer	Thermal printer Paper Width: 80 mm Roll Diameter: 80 mm Print Speed: 200 mm/s Auto cutter	Operating Temp.	0°C to +40°C
Connectivity	Wi-Fi: IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6E, 2.4Ghz/5Ghz/6Ghz, 2x2 MIMO LAN: 1000 Mbps Bluetooth: Bluetooth 5.3, supports BLE	Storage Temp.	-20°C to +60°C
		Operating Humidity	10% to 90% (Non-condensing)
		Certifications & Compliance	CE, CB, FCC, IC, RoHS, WEEE
		Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer

Rev. 2026.06.30

