Cx20 Lite SE

Windows Desktop

Reliable Windows POS Delivering Exceptional Value

Powered by Windows 11 IoT LTSC, Cx20 Lite SE delivers reliable performance, business-grade security, and essential functionality for retail and hospitality all at exceptional value.

- **Immersive Full HD Display Options**
  Features a 15.6" Full HD multi-touch display (1920×1080). An optional 10.1" customer display—standard or interactive with touch and QR camera—enhances engagement and flexibility.

- **Future-Proof Memory & Storage**
  Equipped with 8GB RAM + 256GB storage, expandable to 512GB, enabling fast data processing, secure storage, and room for growth.

- **Enterprise-Grade Windows Platform:**
  Running on Windows 11 IoT LTSC, Cx20 Lite SE ensures long-term stability, enterprise security, and compatibility with a wide ecosystem of applications.

SPECIFICATIONS

Processor	Quad-core Intel, up to 3.6GHz
Operating System	Windows 11 IoT LTSC
Memory	Internal: 8GB RAM + 256GB FLASH 8GB RAM + 512GB FLASH (Optional) 16GB RAM + 256GB FLASH (Optional) 16GB RAM + 512GB FLASH (Optional) **Available SSD capacity may differ from labeled capacity due to system calculations and backup reserves. Actual space is shown in system display*
Main Display	15.6", 1920 × 1080, capacitive multi-touch 178° viewing angle
Customer-Facing Display	Option 1: None Option 2: 10.1" standard CFD (1280 × 800) Option 3: 10.1" premium CFD (1280 × 800, touch panel, camera)
Buttons	1*Power button with indicator light
Camera	Front camera: 2MP, QR code scan (Optional) **Only supported on the 10.1" premium CFD*
Audio	5W, 100dB@1m, Dual speakers , 2*Microphone 1*Headset via 3.5mm audio jack (CTIA&OTMP)
Connectivity	Wi-Fi: IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6E, 2.4Ghz/5Ghz/6Ghz, 2x2 MIMO LAN: 1000 Mbps Bluetooth: Bluetooth 5.3, supports BLE

Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
Power	100V-240V AC, 50-60Hz input; 19V DC, 3.42A output
Dimensions (L × W × H)	361.5 × 234 × 364 mm (Single display version) (Terminal only)
Weight	3.9kg (Single display version) (Terminal only)
Operating Temp.	0°C to +40°C (32°F to 104°F)
Storage Temp.	-20°C to +60°C (-4°F to 140°F)
Operating Humidity	5% to 95% (Non-condensing)
Certifications & Compliance	CE, CB, FCC, IC, RoHS, WEEE, UN 38.3, DGM
Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer

Rev. 2026.10.31

LAVDI

This document is not binding and the specifications above can be modified without prior consent.