

LANDI

Cx30 Cx30 SE

Windows Desktop POS Terminal



Enterprise-scale Windows Performance and Optimized Value.

The Cx30 Series features a deca-core processor with performance of up to **4.4GHz** along with 8GB RAM and 256GB storage, making it perfectly compatible with **Windows 11 IoT**.

- **Intel® Core™ i5 | 10-Core Power**

Top-tier 12 threads, 4.4 GHz with up to 16GB RAM + 512GB SSD for unstoppable multitasking.

- **Windows 11 IoT LTSC Ready**

Enterprise-secure, long-term supported OS built for commercial stability.

- **15.6" FHD Touch + Optional 2nd Screen**

Vivid dual-display interaction with 10.1" or 15.6" customer-facing touchscreen.

- **Modular & Fully Connected**

MSR & Camera-ready with Wi-Fi 6E, BT 5.3 & Gigabit Ethernet for versatile business setups.



| SPECIFICATIONS

Processor	Deca-core Intel i5, up to 4.4GHz	Camera	Front: 2MP, QR code scan (Optional) <i>*Only supported on the 10.1" premium CFD</i>
Operating System	Windows 11 IoT LTSC	Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
Memory	Internal: 8GB RAM + 256GB FLASH 8GB RAM + 512GB FLASH (Optional) 16GB RAM + 256GB FLASH (Optional) 16GB RAM + 512GB FLASH (Optional) <i>*Available SSD capacity may differ from labeled capacity due to system calculations and backup reserves. Actual space is shown in system display.</i>	Power	Cx30:100V-240V AC, 50-60Hz input; 19-20V DC, 4.74A output Cx30 SE:100V-240V AC, 50-60Hz input; 19V DC, 3.42A output
Main Display	15.6", 1920 × 1080, capacitive multi-touch	Dimensions (L × W × H)	361.5 × 234 × 364 mm (Single display version)
Customer-Facing Display	Option 1: None Option 2: 10.1" standard CFD (1280 × 800) Option 3: 10.1" premium CFD (1280 × 800, touch panel, camera) Option 4: 15.6" standard CFD (1920 × 1080, micro USB HOST) Option 5: 15.6" premium CFD (1920 × 1080, touch panel, micro USB HOST)	Weight	Cx30:4.4kg (Single display version) Cx30 SE:3.9kg (Single display version)
Buttons	1*Power button with indicator light	Operating Temp.	0°C to +40°C
Connectivity	Wi-Fi: IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6E, 2.4Ghz/5Ghz/6Ghz, 2x2 MIMO LAN: 1000 Mbps Bluetooth: Bluetooth 5.3, supports BLE	Storage Temp.	-20°C to +60°C
Audio	2*Speaker, 2*Microphone Headset via 3.5mm audio jack	Operating Humidity	10% to 90% (Non-condensing)
Printer (only on Cx30)	Thermal printer Paper Width: 80 mm Roll Diameter: 80 mm Print Speed: 200 mm/s Auto cutter	Certifications & Compliance	CE, CB, FCC, IC, RoHS, WEEE
		Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer

Rev. 2026.06.30



This document is not binding and the specifications above can be modified without prior consent.

