

# M10 SE

Mobile Terminal



## Pocket Size, Robust Mobile Device for Professional Use

- **Front-Facing NFC:** Equipped with front NFC for smooth, customer-facing contactless transactions—perfect for retail and transportation scenarios.
- **Business-Ready:** Streamline tasks with a 5" touchscreen, swappable battery, and support for LANDI Connect—our powerful asset management platform.
- **Durable by Design:** With IP65-rated protection and 1.2m drop resistance, the M10 SE is built for demanding conditions.
- **Fully Connected:** Stay in touch with comprehensive wireless options including 4G LTE, dual-band Wi-Fi, Bluetooth 5.0, GPS, and NFC.
- **Versatile Performance:** Equipped with a quad-core processor, dual SIM slots, and a 5MP camera for QR scanning, it's perfect for retail, logistics, field service, and more.

- Powerful processor for smooth operation ( Quad-core, 2.0GHz)
- Swappable battery on duty (3000mAh/3.7V)
- Comprehensive Connectivity options (2G/3G/4G, Wi-Fi, GPS, Bluetooth 5.0)
- 5M pixels rear camera for convenient QR code reading.



## | SPECIFICATIONS

<b>Processor</b>	A53 Quad-core, up to 2.0GHz	<b>Positioning</b>	AGPS, GPS, Glonass, Beidou, Galileo
<b>OS</b>	Android 13	<b>Camera</b>	Front camera: 0.3M pixels fixed focus camera Rear camera: 5M pixels, autofocus and flashlight
<b>Memory</b>	2GB+16GB Micro SD Card (Up to 2TB)		
<b>Display &amp; Touchscreen</b>	5", 480×854 Capacitive multi-touch	<b>NFC</b>	Android NFC, ISO / IEC 14443, MIFARE, support Type A/B
<b>Scanner</b>	· Optional 1 : NONE · Optional 2 : LANDi Scanner module	<b>SIM</b>	2*SIM
<b>Buttons</b>	1 Power key (Right Side) 2 scan code keys are located on each side	<b>Connection</b>	1 USB-Type C 2.0 2 Pin POGO
<b>Audio</b>	Speaker: 2W 95dB@0.1m MIC: Single-MIC Headset: USB Type-C	<b>Battery</b>	Main Battery: 3.7V/3000mAh, Removable
		<b>Power Supply</b>	5V / 2A
<b>Connectivity</b>	Cellular: 4G fallback 3G and GPRS, Global band Wi-Fi: IEEE 802.11 a/b/g/n/ac 2.4G and 5G Bluetooth: Bluetooth 5.0,support BLE	<b>Accessories (Optional)</b>	· 1+1 Charging Dock · Wrist Strap · Screen Protector · Protective Casing
<b>Protection</b>	IP65 1.2m drop tested *Data from LANDi lab	<b>Environment</b>	Operating temperature: -10℃ to +50℃ Storage temperature: -20℃ to +55℃ Operating humidity: 10% to 90% non-con- densing
<b>Certification</b>	CE, CB, FCC, IC, RoHS, WEEE		

