P10 Countertop

Android payment terminal

*5.5-inch display shown

Design to what matters

Designing smarter to deliver more – for less.

Built with cost-conscious businesses in mind, LANDI P10 Countertop delivers exactly what matters: seamless transactions, essential features and intuitive design – without the extras you don't need.

Countertop efficiency

Stable, connected and ready for everyday business.

Designed for fixed checkout environments, LANDI P10 Countertop combines reliable connectivity, enhanced memory options and dependable performance to keep transactions flowing smoothly throughout the day.

Built to last

Ready for the future, Built on proven foundations.

Engineered for long-term performance, LANDI P10 Countertop is PCI PTS 7.x and Android 14 – offering extended lifecycle support and peace of mind in every transaction.

LANDI www.landiglobal.com

SPECIFICATIONS

Processor	Qualcomm 64-bit quad-core ARM Cortex-A53, 2.0 GHz
System	Android 14 (32 bits)
Memory	**Internal:** 2GB RAM + 8GB FLASH 2GB RAM + 32GB FLASH (Optional) **Expansion:** MicroSD card, up to 2TB
Display	5", 480×854, capacitive multi-touch 5.5", 720×1440, capacitive multi-touch (Optional)
Printer	Thermal printer Paper width: 58 mm Roll diameter: 40 mm Print speed: 100 mm/s max
Button	**Physical:** Power, Menu, Home, Back (For the 5'' main display version) **Physical:** Power; **Virtual:** Menu, Home, Back (For the 5.5'' main display version) (Optional)
Audio	1*Speaker 1*Buzzer (Optional) 1*Headset via USB Type-C port (Optional) 1*Microphone (Optional)
Vibration	Vibration (Optional)
Connectivity	**WAN:** 4G/3G/2G fallback (Optional) **Wi-Fi:** IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz **LAN:** 10/100 Mbps **Bluetooth:** Bluetooth 5.0, supports BLE
Card Reader	**Mag Card:** ISO 1/2/3 track, bi-directional **Smart Card:** EMV Contact L1 & L2, ISO 7816 **Contactless:** EMV Contactless L1 & L2, ISO/IEC 14443 Type A/B, MIFARE, FeliCa 4*LED status indicator

Camera	**Front camera:** 0.3MP with fixed focus (for barcode scanning) 2MP with fixed focus (for barcode scanning) (Optional)
SIM/SAM Slots	2*SAM 1*SIM + 3*SAM (Optional) 1*SIM + 1*eSIM + 2*SAM (Optional)
Ports	1*USB Type-A Host port 1*USB Type-C Device port 1*RJ45 Ethernet port 1*RJ22 Serial port
Power	**Supply:** 100-240V AC 50/60Hz input; 9.0V DC, 2.5A output
Dimensions (L × W × H)	197 × 82 × 70 mm (Terminal only)
Weight	402g (Terminal only)
Operating Temperature	-10°C to +50°C (14°F to 122°F)
Storage Temperature	-20°C to +70°C (-4°F to 158°F)
Operating Humidity	5% to 95% (Non-condensing)
Accessories (Sold separately)	Add-on keypad for visually impaired users
Certifications	**PCI:** PCI PTS 7.x **Payment:** EMVCo Contact L1 & L2, EMVCo Contactless L1 & L2, Mastercard PayPass, Visa payWave, JCB, UPI qUICS, Amex ExpressPay, Discover D-PAS, TQM, PURE, RuPay, CPACE **Regulatory:** CE, CB, FCC, IC, RoHS, UN 38.3, DGM, WEEE

Rev. 2026.09.30

LANDI

This document is not binding and the specifications above can be modified without prior consent.