

P10 Series

Android payment terminal



*5.5-inch display shown

Design to what matters

Designing smarter to deliver more - for less.

Built with cost-conscious businesses in mind, LANDI Android P10 delivers exactly what matters: seamless transactions, essential features and intuitive design - without the extras you don't need.

Flexible deployment

One terminal, two ways to work.

Whether you need Countertop stability or Wireless freedom, LANDI Android P10 adapts to your environment. Same software, same performance - just the setup that fits your business.

Built to last

Ready for the future, Built on proven foundations.

Engineered for long-term performance, LANDI Android P10 device is PCI PTS 7.x and Android 14 - offering extended lifecycle support and peace of mind in every transaction.



SPECIFICATIONS

Form Factor	Wireless	Countertop	Card reader	Mag Card: ISO 1/2/3 track data, bi-directional swiping
Processor	ARM Cortex-A53, Quad-core, 2.0 GHz			IC Card: Support smart IC card, complies with ISO7816 standard EMV L1&L2
OS	Android 14			Contactless: ISO/IEC 14443 Type A&B, Mifare EMV Contactless L1&L2 Felica
Memory	2GB RAM + 8GB FLASH 2GB RAM + 32GB FLASH(Optional)	MicroSD Card (Up to 2TB)		
Display & Touchscreen	5", 854x480 px resolution Capacitive multi-touch 5.5", 1440x720 px resolution (Optional) Capacitive multi-touch		SIM/SIM slots	<ul style="list-style-type: none"> • 2 SIM + 2 SAM • 1 SIM + 3 SAM (Optional) • 1 SIM + 1 eSIM + 2 SAM (Project based)
Printer	80mm/s Paper roll diameter: 40mm Paper width: 58mm		Connection	<ul style="list-style-type: none"> • 1 USB Type-C, OTG • 2 POGO Pins
Button	5": Power button, Menu, Home, Back 5.5": Power button, Virtual buttons: Menu, Home, Back		PSU	5V/2A USB 9V/2.5A DC power
Audio	1 speaker 1 buzzer USB Type-C for Audio output Single MIC (Optional)		Battery	2600mAh/7.2V, removable 3350mAh/7.2V, removable (Optional)
Connectivity	4G with fallback 3G and 2G	(Optional) 4G with fallback 3G and 2G	Optional Accessories	<ul style="list-style-type: none"> • Charging Base • Communication Base
	IEEE802.11 a/b/g/n/ac 2.4GHz and 5GHz			• Add-on keypad for visually impaired users
	Bluetooth 5.0, support BLE			
Positioning	AGPS, GPS, GLONASS, BeiDou, Galileo	None		
Camera	Front: 0.3M pixels, fixed focus, for QR code scanning (Optional) 2M pixels, fixed focus, for QR code scanning (Optional)		Size	197mm x 82mm x 63 mm 197mm x 82mm x 70 mm
	Rear: 0.3M pixels, fixed focus, for code scanning 5M pixels, autofocus and flashlight (Optional)	None	Weight	441g (With battery) 402g
			Environment	Operating temperature: -10°C to +50°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing
			Certification	PCI 7.x/EMVCo Contact L1/L2 CE/CB, ROHS/WEEE, UN38.3 EMVCo Contactless L1 (3.1) Paypass/Paywave/JCB/QUICS/AMEX/DISCOVER/RuPay TQM

*Product design and specifications not finalized. Subject to change.

