

P10 Wireless

Android payment terminal

Unisoc Platform



Design to what matters

Designing smarter to deliver more - for less.

Built with cost-conscious businesses in mind, LANDI P10 Wireless delivers exactly what matters: seamless transactions, essential features and intuitive design - without the extras you don't need.

Flexible deployment

One terminal, endless possibilities.

With full wireless functionality, LANDI P10 Wireless adapts to your environment with ease - delivering reliable performance in a setup that fits your business.

Built to last

Ready for the future, Built on proven foundations.

Engineered for long-term performance, LANDI P10 Wireless device is Android 12 - offering extended lifecycle support and peace of mind in every transaction.



SPECIFICATIONS

Processor	Unisoc 64-bit quad-core ARM Cortex-A53, 1.4 GHz	Card Reader	Mag Card: ISO 1/2/3 track, bi-directional Smart Card: EMV Contact L1 & L2, ISO 7816 Contactless: EMV Contactless L1 & L2, ISO/IEC 14443 Type A/B, MIFARE, FeliCa 4*LED status indicator
OS	Android 12 (32 bits)	SAM/SIM slots	2 SIM + 2 SAM 1 SIM + 3 SAM (Optional) 1 SIM + 1 eSIM + 2 SAM (Optional)
Memory	Internal: 1GB RAM + 8GB FLASH 2GB RAM + 16GB FLASH (Optional) External: MicroSD card, up to 2TB	Connection	1*USB Type-C port 2*Pogo pin
Main Display	5", 480×854, capacitive multi-touch 5.5", 720×1440, capacitive multi-touch (Optional)	Power (Battery Version)	Supply: 100-240V AC 50/60Hz input; 5.0V DC, 2.0A output Battery: 7.2V 2600mAh / 18.72Wh (equivalent to 3.6V 5200mAh), removable; 7.2V 3350mAh / 24.12Wh (equivalent to 3.6V 6700mAh), removable (Optional)
CFD	2", 240×320, non-touch (Optional)	Dimensions (L × W × H)	197 × 82 × 63 mm (Terminal only)
Printer	Thermal printer Paper width: 58 mm Roll diameter: 40 mm Print speed: 100 mm/s max	Weight	346g (Terminal only)
Keys	Physical: Power, Menu, Home, Back (For the 5" main display version) Physical: Power; Virtual: Menu, Home, Back (For the 5.5" main display version) (Optional)	Operating Temperature	Discharging: -10°C to +50°C (14°F to 122°F) Charging: 0°C to +40°C (32°F to 104°F)
Audio	1*Speaker 1*Buzzer (Optional) 1*Headset via USB Type-C port (Optional) 1*Microphone (Optional)	Storage Temperature	-20°C to +70°C (-4°F to 158°F)
Vibration	Vibration (Optional)	Operating Humidity	5% to 95% (Non-condensing)
Connectivity	WAN: 4G/3G/2G fallback Wi-Fi: IEEE 802.11 b/g/n, 2.4Ghz IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz (Optional) Bluetooth: Bluetooth 4.2, supports BLE (For 2.4G Wi-Fi module) Bluetooth 5.0, supports BLE (For dual Wi-Fi module) (Optional)	Accessories (Optional)	Charging base Functional base Add-on keypad for visually impaired users
Positioning	GPS, GLONASS, BeiDou, Galileo	Certification	PCI: PCI PTS 7.x Payment: EMVCo Contact L1 & L2, EMVCo Contactless L1 & L2, Mastercard PayPass, Visa payWave, JCB, UPI qUICS, Amex ExpressPay, Discover D-PAS, TQM, PURE, RuPay Regulatory: CE, CB, FCC, RoHS, WEEE, UN 38.3, DGM, BIS, WPC, DJID, NBTC
Camera	Front camera: 0.3MP with fixed focus (for barcode scanning) 2MP with fixed focus (for barcode scanning) (Optional) Rear camera: 0.3MP with fixed focus (for barcode scanning) 5MP with autofocus & flash (Optional)		

Rev. 2026.09.30



This document is not binding and the specifications above can be modified without prior consent.

