

P10 Wireless

Android payment terminal



Design to what matters

Designing smarter to deliver more - for less.

Built with cost-conscious businesses in mind, LANDI Android P10 delivers exactly what matters: seamless transactions, essential features and intuitive design - without the extras you don't need.

Wireless freedom

Take payments wherever business happens.

Designed for mobility and flexibility, LANDI Android P10 Wireless combines multiple connectivity options with lightweight portability, enabling smooth payment experiences at the counter, tableside or on the move.

Built to last

Ready for the future, Built on proven foundations.

Engineered for long-term performance, LANDI Android P10 device is PCI PTS 7.x and Android 12 - offering extended lifecycle support and peace of mind in every transaction.



SPECIFICATIONS

Processor	P10 Q: 64-bit quad-core ARM Cortex-A53, 2.0 GHz P10 U: 64-bit quad-core ARM Cortex-A53, 1.4 GHz	Positioning	AGPS, GPS, GLONASS, BeiDou, Galileo
		Ports	1*USB Type-C port 2*POGO pins
System	P10 Q: Android 14 P10 U: Android 12	Power	Supply: 100-240V AC 50/60Hz input 5.0V DC, 2.0A output Battery: 7.2V 2600mAh / 18.72Wh, removable 7.2V 3350mAh / 24.12Wh, removable (Optional)
		Card reader	Mag Card: ISO 1/2/3 track, bi-directional Smart card: EMV Contact L1 & L2, ISO 7816 Contactless: EMV Contactless L1 & L2, ISO/IEC 14443 Type A/B, MIFARE, FeliCa 4*LED status indicator
Memory	Internal: 2GB RAM + 8GB FLASH (P10-Q) 1GB RAM + 8GB FLASH (P10-U) (Optional) 2GB RAM + 16GB FLASH (P10-U & P10-Q) (Optional) 2GB RAM + 32GB FLASH (P10-Q) (Optional) Expansion: MicroSD card, up to 2TB	SIM/SAM Slots	2*SIM + 2*SAM 1*SIM + 3*SAM (Optional) 1*SIM + 1*eSIM + 2*SAM (Optional)
		Dimensions	197 × 82 × 63 mm
Display	5", 480×854, capacitive multi-touch 5.5", 720×1440, capacitive multi-touch (Optional)	Weight	346g (Terminal only)
		Operating Temp.	Discharging: -10°C to +50°C Charging: 0°C to +40°C
Button	Physical: Power, Menu, Home, Back Physical: Power; Virtual: Menu, Home, Back (Optional)	Storage Temp.	-20°C to +70°C
		Operating Humidity	10% to 90% (Non-condensing)
Camera	Front: 0.3MP with fixed focus (for barcode scanning) 2MP with fixed focus (for barcode scanning) (Optional) Rear: 0.3MP with fixed focus (for barcode scanning) 5MP with autofocus & flash (Optional)	Certifications & Compliance	PCI: PCI PTS 7.x Payment: EMVCo Contact L1 & L2, EMVCo Contactless L1 & L2, Mastercard PayPass, Visa payWave, JCB, UPI qUICS, Amex ExpressPay, Discover D-PAS, TQM Regulatory: CE, CB, FCC, IC, RoHS, WEEE, UN 38.3
Printer	Thermal printer Paper width: 58 mm Roll diameter: 40 mm Print speed: 80 mm/s	Accessories (Sold separately)	Charging base Functional base Add-on keypad for visually impaired users
Audio	1*Speaker 1*Buzzer , 1*Microphone , Headset via USB Type-C port		
Connectivity	WAN: 4G/3G/2G fallback Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz IEEE 802.11 b/g/n, 2.4Ghz (Optional) Bluetooth: Bluetooth 5.0, supports BLE (P10-Q) Bluetooth 5.0, supports BLE (P10-U with dual Wi-Fi) (Optional) Bluetooth 4.2, supports BLE (P10-U 2.4G Wi-Fi) (Optional)		

