

# P20 & P30 ACCESSORY OPTIONS

## Charging Base, Functional Base & Magic Hub



### | SPECIFICATIONS

#### Charging Base

<b>PSU</b>	TYPE-C standard charging port, 5.0V DC, 2.0A
<b>Connection</b>	Base includes POGO pins, supports charging for P20/P30 host device
<b>Size</b>	206 mm × 92 mm × 47 mm
<b>Weight</b>	137g
<b>Environment</b>	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing

#### Functional Base

<b>PSU</b>	USB Host Output: 5.0V DC, 0.5A Charging Output: 5.0V DC, 1.0A (1.5A when USB Host is inactive) Adapter: 100-240V AC, 50/60Hz (Input); 5.0V DC, 2.0A (Output)		
<b>LED</b>	Power Indicator Green: Base powered on Power Indicator Unlit: Base powered off Ethernet Indicator Green: Ethernet connected Ethernet Indicator Unlit: No Ethernet COMM Indicator Solid Green: Base to be associated COMM Indicator Blinks Green: Base upgrading STAT Indicator Solid Green: Base associated and connected with P20/P30 STAT Indicator Blinks Green: Base associated but disconnected with P20/P30		
<b>Connection</b>	USB Type-C power port *1 RJ45 Ethernet port *1	RJ22 serial port *1 RJ45 serial port *1	USB Type-A HOST port supporting USB2.0 *1 USB Type-C DEVICE port supporting USB2.0 *1
<b>Size</b>	206 mm × 92 mm × 47 mm		
<b>Weight</b>	184g		
<b>Environment</b>	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing		





Base with Scanner



Magic Hub

## SPECIFICATIONS

### Charging Base with Scanner

<b>PSU</b>	TYPE-C standard charging port, 5.0V DC, 2.0A
<b>Connection</b>	Base includes POGO pins, supports charging for P20/P30 host device
<b>Size</b>	244 mm × 90 mm × 73 mm
<b>Weight</b>	233g
<b>Environment</b>	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing

### Functional Base with Scanner

<b>PSU</b>	USB Host Output: 5.0V DC, 0.5A Charging Output: 5.0V DC, 1.0A Adapter: 100-240V AC, 50/60Hz (Input); 5.0V DC, 2.0A (Output)		
<b>LED</b>	Power Indicator Green: Base powered on Power Indicator Unlit: Base powered off Ethernet Indicator Green: Ethernet connected Ethernet Indicator Unlit: No Ethernet COMM Indicator Solid Green: Base to be associated COMM Indicator Blinks Green: Base upgrading STAT Indicator Solid Green: Base associated and connected with P20\P30 STAT Indicator Blinks Green: Base associated but disconnected with P20\P30		
<b>Connection</b>	USB Type-C power port *1 RJ45 Ethernet port *1	RJ22 serial port *1 RJ45 serial port *1	USB Type-A HOST port supporting USB2.0 *1 USB Type-C DEVICE port supporting USB2.0 *1
<b>Size</b>	244 mm × 90 mm × 73 mm		
<b>Weight</b>	287g		
<b>Environment</b>	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing		

### Magic Hub

<b>PSU</b>	Power Input: 5.0V DC / 4.0A for non-battery version terminals; 5.0V DC / 2.0A for battery version terminals USB-A 2.0 Output: 5.0V / 0.5A per port RJ22 Serial Output: 5.0V / 0.5A	
<b>Connection</b>	1*USB Type-C DEVICE port supporting USB2.0 2*USB Type-A HOST port supporting USB2.0	1*RJ22 Serial port 1*RJ45 Ethernet port
<b>Size</b>	107.9 mm × 24 mm × 36.5 mm	
<b>Weight</b>	90g	
<b>Environment</b>	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing	

