

# P30-Q

Android payment terminal



| Qualcomm Edition

**High-performance design for payment  
and business convergence.**

**LANDI**

[www.landiglobal.com](http://www.landiglobal.com)

## • Performance without limits

Faster check-outs. Smoother operations

With next-gen processing power, LANDI P30 handles demanding apps, multitasking tasks and high transaction volume - without breaking a sweat.

## • A larger screen for a better experience

More space. More clarity. More confidence

A stunning 6.5" display gives your staff and customers more room to see, sign and interact.

## • Sleek look, serious business

Looks as smart as it works.

Its sleek, ergonomic design reinforces your brand's image - making every transaction feel like a premium experience.



# | SPECIFICATIONS

<b>Processor</b>	64-bit ARM Cortex Octa-Core, 4*A73, 2.4GHz + 4*A55, 1.9GHz	<b>Camera</b>	Front: 0.3M pixels, fixed focus, for QR code scanning
<b>OS</b>	Android 14		2M pixels, fixed focus, for QR code scanning (Optional)
<b>Memory</b>	2GB RAM + 32GB FLASH (Optional) 4GB RAM + 64GB FLASH Micro SD Card (Up to 2TB)		Rear: 5M pixels, autofocus and flashlight 8M pixels, autofocus and flashlight (Optional)
<b>Display &amp; Touchscreen</b>	6.5", 1600x720 px resolution Capacitive multi-touch	<b>Printer</b>	Thermal 80mm/s Paper roll diameter: 40mm Paper width: 58mm
<b>Keypad</b>	1 Power key Volume+ key / Volume- key	<b>Connection</b>	1 USB Type-C (Host & Device mode) 2 POGO Pins
<b>Audio</b>	1 Speaker, 1 Buzzer USB-C for Audio output, Dual MIC (Optional)	<b>Size</b>	207mm x 84mm x 67mm
<b>Connectivity</b>	4G with fallback 3G and 2G Wi-Fi: IEEE 802.11 a/b/g/n/ac 2.4GHz and 5GHz Bluetooth 5.0, support BLE	<b>Weight</b>	430g (With battery)
<b>Card reader</b>	Mag Card: ISO 1/2/3 track data, bi-directional swiping IC Card: Support smart IC card, complies with ISO7816 standard EMV L1&L2 Contactless: ISO/IEC 14443 Type A&B, Mifare EMV Contactless L1&L2 Felica	<b>Environment</b>	Operating temperature: -10°C to +50°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing
<b>SIM/SIM slots</b>	2 SIM + 2 SAM 1 SIM + 3 SAM (Optional) 1 SIM + 1 eSIM + 2 SAM (Project based)	<b>Certification</b>	PCI PTS 6.X EMVCo Contact L1/L2 EMVCo Contactless L1 Paypass, Paywave, AMEX, JCB, Discover Quics, TQM CE, ROHS, WEEE
<b>Positionning</b>	A-GPS, GPS, GLONASS, BeiDou, Galileo	<b>Optional Accessories</b>	Charging base Communication base Magic Hub Add-on keypad for visually impaired users
<b>Battery</b>	2600mAh/7.2V, removable 3350mAh/7.2V, removable (Optional)		
<b>PSU</b>	5V/2A USB		

**LANDI**

This document is not binding and the specifications above can be modified without prior consent.

