

# P30-U

Android payment terminal



UNISOC Edition

High-performance design for payment  
and business convergence.

- **Performance without limits**

Faster check-outs. Smoother operations

With next-gen processing power, LANDI P30 handles demanding apps, multitasking tasks and high transaction volume - without breaking a sweat.

- **A larger screen for a better experience**

More space. More clarity. More confidence

A stunning 6.5" display gives your staff and customers more room to see, sign and interact.

- **Sleek look, serious business**

Looks as smart as it works.

Its sleek, ergonomic design reinforces your brand's image - making every transaction feel like a premium experience.



## | SPECIFICATIONS

<b>Processor</b>	64-bit ARM Cortex Octa-Core, 4*A75, 1.6 Ghz + 4*A55, 1.6 GHz	<b>Camera</b>	Front: 0.3M pixels, fixed focus, for QR code scanning 2M pixels, fixed focus, for QR code scanning (Optional) Rear: 5M pixels, autofocus and flashlight 8M pixels, autofocus and flashlight (Optional)
<b>OS</b>	Android 14	<b>Printer</b>	Thermal 40mm×58mm
<b>Memory</b>	2GB + 32GB 4GB + 64GB (Optional) Micro SD Card (Up to 2TB)	<b>Connection</b>	1*USB Type-C 1*USB Type-C for Magic Hub (Optional) 2*POGO pins
<b>Display &amp; Touchscreen</b>	6.5", 1600x720 px capacitive multi-touch	<b>Size</b>	207mm × 84mm × 67mm
<b>Keypad</b>	1*Power key Volume + key / Volume - key	<b>Weight</b>	430g (With battery)
<b>Audio</b>	1*Speaker 1*Buzzer (Optional) USB-C for Audio output Dual MIC (Optional)	<b>Environment</b>	Operating temperature: -10 C to +50 C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing
<b>Connectivity</b>	4G with fallback 3G and 2G Wi-Fi: IEEE8.2.11 a/b/g/n/ac 2.4 GHz and 5 GHz Bluetooth 5.0, support BLE	<b>Certification</b>	PCI 7.x EMVCo Contact L1/L2, EMVCo Contactless L1, Paypass/Paywave/JCB/QUICS/AMEX/-DISCOVER/TQM CE/CB/FCC/IC/ROHS/WEEE, UN38.3
<b>Card reader</b>	Mag Card: ISO 1/2/3 track data, bi-directional swiping IC Card: Support smart IC card, complies with ISO7816 standard EMV L1&L2 Contactless: ISO/IEC 14443 Type A&B, Mifare EMV Contactless L1&L2 Felica	<b>PSU</b>	5V/2A
<b>SAM/SIM slots</b>	2*SIM + 2*SAM 1*SIM + 3*SAM (Optional) 1*SIM + 1*eSIM + 2*SAM (Optional)	<b>Scanner</b>	Professional scanner (Optional)
<b>Positioning</b>	AGPS, GPS, Glonass, Beidou, Galileo	<b>Optional Accessories</b>	Charging Base Functional Base
<b>Battery</b>	2600mAh/7.2V, removable 3350mAh/7.2V, removable (Optional)		

\*Payment solutions are subject to some restrictions until mid-January 2026.

**LANDI**

This document is not binding and the specifications above can be modified without prior consent.

