

P30 Series

Android payment terminal



High-performance design for payment
and business convergence.

- **Performance without limits**

Faster check-outs. Smoother operations

With next-gen processing power, LANDI P30 handles demanding apps, multitasking tasks and high transaction volume - without breaking a sweat.

- **A larger screen for a better experience**

More space. More clarity. More confidence

A stunning 6.5" display gives your staff and customers more room to see, sign and interact.

- **Sleek look, serious business**

Looks as smart as it works.

Its sleek, ergonomic design reinforces your brand's image - making every transaction feel like a premium experience.



| SPECIFICATIONS

Processor	P30 Q: 64-bit octa-core ARM Cortex (4x 2.4 GHz A73 + 4x 1.9 GHz A55) P30 U: 64-bit octa-core ARM Cortex (4x 1.6 GHz A75 + 4x 1.6 GHz A55)	Card reader	Mag Card: ISO 1/2/3 track, bi-directional Smart card: EMV Contact L1 & L2, ISO 7816 Contactless: EMV Contactless L1 & L2, ISO/IEC 14443 Type A/B, MIFARE, FeliCa 4*LED status indicator
System	Android 14	SIM/SAM Slots	2*SIM + 2*SAM 1*SIM + 3*SAM (Optional) 1*SIM + 1*eSIM + 2*SAM (Optional)
Memory	Internal: 2GB RAM + 32GB FLASH 4GB RAM + 64GB FLASH (Optional) Expansion: MicroSD card, up to 2TB	Dimensions	207 × 84 × 67 mm
Display	6.5", 720×1600, capacitive multi-touch	Weight	340g (Terminal only)
Button	Physical: Power, Volume Up/Down Virtual: Menu, Home, Back	Operating Temp.	Non-Battery Version: -10°C to +50°C Battery Version: Discharging: -10°C to +50°C Charging: 0°C to +40°C
Camera	Front: 2MP with fixed focus (for barcode scanning) Rear: 5MP with autofocus & flash 8MP with autofocus & flash (Optional)	Storage Temp.	-20°C to +70°C
Printer	Thermal printer Paper width: 58 mm Roll diameter: 40 mm Print speed: 80 mm/s	Operating Humidity	10% to 90% (Non-condensing)
Audio	1*Speaker, Headset via USB Type-C port 1*Buzzer (Optional), 2*Microphone (Optional)	Certifications & Compliance	PCI: PCI PTS 7.x Payment: EMVCo Contact L1 & L2, EMVCo Contactless L1 & L2, Mastercard PayPass, Visa payWave, JCB, UPI qUICS, Amex ExpressPay, Discover D-PAS, TQM Regulatory: CE, CB, FCC, IC, RoHS, WEEE, UN 38.3
Connectivity	WAN: 4G/3G/2G fallback Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz Bluetooth: Bluetooth 5.0, supports BLE	Accessories (Sold separately)	Magic Hub Charging base Functional base Add-on keypad for visually impaired users
Positioning	AGPS, GPS, GLONASS, BeiDou, Galileo		
Ports	1*USB Type-C port 2*POGO pins 1*USB Type-C port for Magic Hub (Optional)		
Power	Battery Version Supply: 100-240V AC 50/60Hz input; 5.0V DC, 2.0A output Battery: 7.2V 2600mAh / 18.72Wh, removable; 7.2V 3350mAh / 24.12Wh, removable (Optional) Non-Battery Version Supply: 100-240V AC 50/60Hz input; 5.0V DC, 4.0A output		

